

OPTIONS

Mounting method

• to be grouted in

Number of parking spaces

- spaces for 3 bicycles
- space for 4 bicycles
- spaces for 5 bicycles
- space for 6 bicycles
- space for 7 bicycles

DESCRIPTION

Bicycle rack, model 05.056 from the contemporary series, features a curved steel tube frame with attached bike parking racks made of bars. The number of racks can be specified by the buyer, ranging from a minimum of 3 to a maximum of 7. This rack is securely installed in a concrete base to prevent damage. The unique design of this model is popular in modern urban environments, though a traditional style option is also available.

GENERAL TECHNICAL DATA

Dimensions


- width: 16 1/2 in
- length: 78 ³/4 in
- height from ground surface: 32 3/4 in
- height with anchor section: 56 ¹/₄ in


Materials

- steel tubes
- steel bars
- steer bars



In accordance with the Polish Law on Copyright and Related Rights of 04.02.1994 (Offcial Journal of Laws No. 24, item 83, corrected: Journal of Laws No. 43, item 170) and in accordance with the EU copyright legislation including all EU directives and regulations on copyright , Zano Mirosław Zarotynski Company, reserves the copyright of drawings, descriptions, 3D models, renderings, graphics, content contained in offers, attachments to offers and all other documents. Its content is the intellectual property of ZANO Miroslaw Zarotinski company. The use of author's ideas, solutions, copying, distribution of photos, graphics or fragments of graphics, descriptive texts, for profit, without the permission of the author - ZANO Miroslaw Zarotynski company - is prohibited and constitutes a copyright infringement and is punishable.








MOUNTING DIAGRAMS (E, F, G) FOR MOUNTING TO THE FOUNDATION

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

G


The size of the foundation depends on local foundation conditions.



INSTALLATION TO PAVING WITH FOUNDATION

Installation description

- 1. ZANO product
- 2. Stone paving / concrete paving / stone slabs / concrete slabs
- **3.** Sand ballast (approximately 2 4 cm)
- 4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 5. Local land



MOUNTING TO CONCRETE FOUNDATION

Installation description

- 1. ZANO product
- 2. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 3. Local land

MOUNTING TO CONCRETE FOUNDATION

3

2

Installation description

- 1. ZANO product
- 2. Fixed restrained surface, such as concrete or asphalt
- Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
- 4. Stone aggregate substructure
- 5. Sand ballast (approximately 2 4 cm)
- 6. Local land