OPTIONS

Mounting method
- free-standing
- to screw

Contribution
- uncontributed

DESCRIPTION

The Altus 15.454.4 recycling trash bin features four compartments for sorting waste. It lacks internal liners and its sides are constructed of Plexiglas, allowing for clear visibility of the contents when translucent bags are used. This design helps meet specific anti-terrorism and bomb safety standards. The bin's framework is crafted from steel flat bars, available in either stainless steel or carbon steel, which can be painted in any RAL color chosen by the customer.

Explore more **bins from the Altus collection**. Options include bins with sides made of steel, wood, HPL board, and architectural concrete.

GENERAL TECHNICAL DATA

Dimensions
- width: 59 ³/₄ in
- height: 40 ¹/₄ in
- depth: 15 in

Capacity
- number of containers: 4 pcs
- capacity of one container: 13 ¹/₄ gal

Materials
- Profiles in stainless steel or optional painted carbon steel
- walls - acrylic glass (plexiglass)

ZANO

Product:
Altus recycling garbage can
Catalog number: **15.452.4**
Designer: Iwona Żaczek

td>

NOTE: The drawings do not reflect the actual dimensions of the foundation. These are only sample installation diagrams taking into account the type of anchoring and the material of the substrate to which to attach the furniture.

The size of the foundation depends on local foundation conditions.

INSTALLATION TO PAVING WITH FOUNDATION

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
7. Local land

MOUNTING TO PAVING

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Stone paving / concrete paving / stone slabs / concrete slabs
4. Sand ballast (approximately 2 - 4 cm)
5. Stone aggregate substructure
6. Local land

MOUNTING TO CONCRETE / ASPHALT

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Fixed restrained surface, such as concrete or asphalt
4. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
5. Stone aggregate substructure
6. Sand ballast (approximately 2 - 4 cm)
7. Local land

MOUNTING TO CONCRETE FOUNDATION

Installation description

1. ZANO product
2. Quick-attachment / quick-attachment or chemical anchor
3. Concrete foundation of C16/20 class (top surface of concrete 10 cm below paving surface)
4. Local land